

# BeaconTag Specifications



August 2018

**Pinmicro K.K. Confidential and Proprietary**

**Restricted Distribution:** This documentation is the property of Pinmicro K.K. Not to be used, copied, reproduced in whole or in part, nor its contents revealed in any manner to others without the prior written permission of Pinmicro K.K.

In case of any queries please contact us on [support@pinmicro.com](mailto:support@pinmicro.com)

# BeaconTag


---

BeaconPlus Tag is a small wireless Bluetooth low energy device that broadcasts radio signals, which most of the BLE/iBeacon enabled devices can detect. You can determine precise location of your customer when they are in the range of your BeaconPlus beacon and exchange targeted information with him securely. BeaconPlus beacon has a long life of up to 2 years with a single coin cell.



## Physical Dimensions

---



## BeaconTag Specifications

	Property	Value	Unit
<b>Dimension and Weight</b>	Height	37	mm
	Width	37	mm
	Thickness	6.2	mm
	Weight	10	gm
<b>Power</b>	Battery	CR2032	
<b>Radio : Bluetooth</b>	RF protocol	BLE	
	Frequency band	2.4	GHz
	Transmitting power	+4,+3,0,-4,-8,-12,-16,-20,-40	dB
	Receiver Sensitivity	-93	dB
	Case Material	ABS plastic	
	Battery life*	2	years
	Operating temperature	-10 to +60	°C
	Operating voltage	3	V

\* Depends upon transmission interval and transmission power